

Tiandy



TC-R3440 Spec: I/B/N

H.265 4HDD 40ch NVR

Pro Series



KEY FEATURES

HD Input

- S+265/H.265/H.264 video formats
- Connectable to the third-party network cameras
- Up to 40 IP cameras can be connected
- Supports live view, storage, and playback of the connected camera at up to 12MP resolution

HD Output

- HDMI and VGA independent outputs
- HDMI Video output at up to 4K (3840 × 2160) resolution

HD Storage

- 4 SATA interfaces connectable for recording and backup, up to 10TB for each HDD
- S+265 compression effectively reduces the storage space and costs by up to 75%

HD Transmission

- 2 × RJ45 self-adaptive 10/100/1000 Mbps network interfaces

Various Applications

- Centralized management of IP cameras, including configuration, information import/export, real-time information display, two-way audio, upgrade, etc.
- Connectable to smart IP cameras from Tiandy and the recording, playing back, and backing up of VCA alarms can be realized
- VCA detection alarm is supported
- Smart search for the selected area in the video and smart playback to improve the playback efficiency
- Web6 supports plug-in-free browsing and can preview videos on all browsers



SPECIFICATIONS

| Input | |
|---------------------------|--|
| Video Input | 40-ch |
| Max Resolution | 12MP |
| Two-way Audio Input | 1-ch, 3.5mm |
| Bandwidth | Income 400Mbps; Outcome 200Mbps |
| Output | |
| HDMI/VGA Output | HDMI: 1-ch, 3840×2160, 2560×1600, 2560×1440, 1920×1080, 1280×720, 800×600, 1024×768, 1366×768, 1440×900, 1280×800 VGA: 1-ch, 1920×1080, 1280×720, 800×600, 1024×768, 1366×768, 1440×900, 1280×800 |
| Screen Split | 1/3/4/6/8/9/10/13/16/20/25/36/40/64 |
| Audio Output | 1×RCA |
| Decoding | |
| Decoding Format | S+265/H.265/H.264 |
| Recording Resolution | 12MP/8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF |
| Preview Capability | 2×12MP, 4×4K, 5×5MP, 8×4MP, 16×1080P, 32×720P, 40×4CIF |
| Synchronous Playback | 2×12MP, 4×4K, 5×5MP, 8×4MP, 16×1080P, 16×720P |
| Records Encryption | Yes |
| Hard Disk | |
| SATA | 4 SATA interfaces for 4 HDDs |
| Capacity | Up to 10TB for each HDD |
| eSATA Interface | N/A |
| Array Type | N/A |
| External Interface | |
| Network Interface | 2×RJ45 self-adaptive 10/100/1000 Mbps network interfaces |
| USB Interface | 1×USB 2.0, 1×USB 3.0 |
| Serial Interface | 1×RS485, 1×RS232 |
| Alarm In/Out | 16/4 |
| Reliability | |
| N+M Hot Standby | N/A |
| ANR | N/A |
| General | |
| Web Version | Web6 |
| Language | English, Russian, Spanish, Korean, Italian, Turkish, Simple Chinese, Traditional Chinese, Thai, French, Polish, Dutch, Hebraism (UI), Farsi (UI) |
| Operating Conditions | -10°C ~ 55°C, 10%~90% RH |
| Power Supply | DC12V 5A |
| Consumption (without HDD) | ≤40W (without HDD) |
| Chassis | 1.5U |
| Dimensions | 75×440×347 mm (2.95×17.32×13.66 inch) |
| Weight (without HDD) | 3.8Kg (8.38lb) |

AVAILABLE MODEL


TC-R3440 SPEC: I/B/N

Tiandy

DIMENSIONS (Unit: mm)



Physical Interfaces



DISTRIBUTED BY



Tiandy Technologies Co., Ltd.

Email: sales@tiandy.com Tel: +86-22-58596065
Website: en.tiandy.com Fax: +86-22-58596048